



FortiGate/FortiWiFi® 90D Series

Enterprise-Grade Protection for Distributed Network Locations

The FortiGate/FortiWiFi 90D Series are compact, all-in-one security appliances that deliver Fortinet's Connected UTM. Ideal for remote, customer premise equipment (CPE) and retail networks, these appliances offer the network security, connectivity, and performance you need at a single low per-device price.



You get advanced threat protection, including firewall, application control, advanced threat protection, IPS, VPN, and web filtering, all from one device that's easy to deploy and manage. With its comprehensive management console, remote provisioning and wide range of connectivity options you have an easy-to-deploy, easy-to-manage solution that's great for a centrally managed infrastructure.

Reduce the need for additional wireless access points by integrating a high-bandwidth "fat-client" into your FortiGate with the FortiWiFi 90D. It's also a great option to secure mobile devices in BYOD environments with automatic device identification and customizable access and security policies.

You'll appreciate features like WAN Optimization, Data Archiving and VDOMs for your distributed networks. VDOMs on the FortiGate/FortiWiFi 90D, let you segment networks to enable guest and employee access, or protect things like cardholder data to meet compliance standards like PCI and HIPAA.

Built on the foundation of the FortiASIC System on a Chip 2 (SoC2) and FortiOS 5, the 90D series provides an integrated set of essential security technologies to protect all of your applications and data. You get the industry's best firewall plus the latest in Advanced Threat Protection, Intrusion Protection, Web-filtering and many new features like Sandboxing, Feature Select Options for simplifying configurations and deployments, and Contextual Visibility for enhanced reporting and management.

Key Features & Benefits

Unified Security	Multi-threat protection from a single device increases security and lowers costs for remote locations
Simplified Licensing	Unlimited user licensing and comprehensive features
Multi-Port Interfaces	Multiple network interfaces and optional wireless connectivity enable data segmentation for compliance and flexible deployment



Enterprise-Class Protection that's Easy to Deploy and Manage

- 3.5 Gbps throughput performance delivers fast network response
- Integrated switch and options for PoE simplify your network infrastructure
- Up to 2x WAN and 14x LAN (4x Power over Ethernet ports on PoE models)
- Runs on FortiOS 5 the most powerful security operating system in the world delivers more security to fight advanced threats, more control to secure mobile devices, and more intelligence to build secure policies







FortiGate/FortiWiFi 90D(-POE)







- 1. Console Port
- 2. USB Management Port
- 3. 2x USB Ports
- 4. 14x GE RJ45 Switch Ports / 10x GE RJ45 Switch and 4x RJ45 PoE Ports on PoE Models
- 5. 2x GE RJ45 WAN Ports

FortiGate 94D-POE





- 1. USB Management Port
- 2. 2x GE RJ45 WAN Ports
- 3. 24x GE RJ45 Switch Ports
- 4. 24x FE RJ45 PoE Ports
- 5. 2x GE SFP DMZ Slots
- 6. Console Port
- 7. USB Port



Powered by FortiASIC SOC2

- Combines a RISC-based CPU with Fortinet's proprietary FortiASIC™ content and network processors for unmatched performance
- Simplifies appliance design and enables breakthrough performance for smaller networks
- Supports firewall acceleration across all packet sizes for maximum throughput
- Delivers accelerated UTM content processing for superior performance and protection
- Accelerates VPN performance for high speed, secure remote access

Install in Minutes with FortiExplorer

The FortiExplorer™ wizard enables you to easily and quickly set up and configure FortiGate and FortiWiFi platforms with easy-to-follow instructions. The application runs on Windows, Mac OS X desktops and laptops as well as popular mobile devices. Simply connect to the appropriate USB port on the appliance, and be fully protected in minutes.

3G/4G WAN Connectivity

The FortiGate/FortiWiFi 90D Series includes USB ports that allow you to plug in a compatible third-party 3G/4G USB modem, providing additional WAN connectivity or a redundant link for maximum reliability.

Compact and Reliable Form Factor

Designed for small environments, you can place it on a desktop or wall-mount it. It is small, lightweight yet highly reliable with superior MTBF (Mean Time Between Failure), minimizing the chance of a network disruption.

Superior Wireless Coverage

A built-in dual-band, dual-stream access point with internal antennas is integrated on the FortiWiFi 90D and provides speedy 802.11n coverage on both 2.4 GHz and 5 GHz bands. The dual-band chipset addresses the PCI-DSS compliance requirement for rogue AP wireless scanning, providing maximum protection for regulated environments.

FortiOS — The World's Most Advanced Security Operating System

Feature Select

Instantly fine-tunes the FortiGate based on desired deployment needs using feature presets. Simplifies user administration and configurations while providing flexibility for different deployment modes.

Contextual Visibility

Presents critical deep insights into historic or real-time network activities with data on threat details, IPs, users, devices, applications and more. Allows administrators to quickly understand threats and stop them.

Advanced Security

Multiple advanced technologies can be coordinated to look for and stop today's blended, targeted or unknown attacks. Efficient packet handling improves performance while lowering latencies and reducing network complexities.

For complete, up-to-date and detailed feature set, please refer to the Administration Handbook and FortiOS Datasheet

Industry Validation

The FortiGate family of physical and virtual appliances has earned more certifications than any other vendor by consistently meeting rigorous third-party standards. Our industry-leading technology provides you with air-tight security which you can safely count on.

World-Class Technical Support and Documentation

Fortinet FortiCare support offerings provide comprehensive global support for all Fortinet products and services. You can rest assured your Fortinet security products are performing optimally and protecting your users, applications, and data around the clock.

More Protection and Better ROI

The FortiGate constantly evolves itself in its mission to provide more value for users. Extended features such as WiFi controller, integrated token server, endpoint control and WAN optimization add more security to organizations without incurring additional cost.

Complete and Real-time Security

Fortinet FortiGuard Subscription Services provide automated, real-time, up-to-date protection against the latest security threats. Our threat research labs are located worldwide, providing 24x7 updates when you most need it.



FortiOS Dashboard — Single Pane of Glass Management

ORDER INFORMATION

Product S	SKU	Description
FortiGate 90D	G-90D	16x GE RJ45 ports (2x WAN ports, 14x Switch ports), 32 GB onboard storage. Max managed FortiAPs (Total / Tunnel) 32 / 16.
FortiWiFi 90D F	WF-90D	16x GE RJ45 ports (2x WAN ports, 14x Switch ports), Wireless (802.11a/b/g/n), 32 GB onboard storage. Max managed FortiAPs (Total / Tunnel) 32 / 16.
FortiGate 90D-P0E	G-90D-P0E	16x GE RJ45 ports (including 2x WAN ports, 10x Switch ports, 4x PoE ports), 32 GB SSD onboard storage. Max managed FortiAPs (Total / Tunnel) 32 / 16.
FortiWiFi 90D-P0E	WF-90D-POE	16x GE RJ45 ports (including 2x WAN ports, 10x Switch ports, 4x PoE ports), Wireless (802.11a/b/g/n), 32 GB SSD onboard storage. Max managed FortiAPs (Total / Tunnel) 32 / 16.
FortiGate 94D-P0E	G-94D-POE	26x GE RJ45 ports (including 24x Switch ports, 2x WAN ports), 24x PoE FE ports, 2x DMZ GE SFP slots. Max managed FortiAPs (Total / Tunnel) 32 / 16.

SPECIFICATIONS

	FORTIGATE 90D	FORTIWIFI 90D	FORTIGATE 90D-P0E	FORTIWIFI 90D-P0E	FORTIGATE 94D-POE		
Hardware Specifications							
GE RJ45 WAN Ports			2				
GE RJ45 Switch Ports	14	14	10	10	24		
GE RJ45 PoE Ports	_	_	4	4	_		
FE RJ45 PoE Ports	-	_	_	_	24		
GE SFP DMZ Slots	_	_	_	_	2		
Wireless Interface	_	802.11 a/b/g/n	_	802.11 a/b/g/n	_		
USB Ports (Client / Server)	1/2	1/2	1/2	1/2	1/1		
Console (RJ45)			1				
Internal Storage			32 GB				
System Performance							
Firewall Throughput (1518 / 512 / 64 byte UDP packets)			3.5 / 3.5 / 3.5 Gbps				
Firewall Latency (64 byte UDP packets)			4 μs				
Firewall Throughput (Packets Per Second)			5.3 Mpps				
Concurrent Sessions (TCP)			2 Million				
New Sessions/Sec (TCP)			4,000				
Firewall Policies			5,000				
Psec VPN Throughput (512 byte packets)			1 Gbps				
Gateway-to-Gateway IPsec VPN Tunnels			200				
Client-to-Gateway IPsec VPN Tunnels			1,000				
SSL-VPN Throughput			35 Mbps				
Concurrent SSL-VPN Users (Recommended Maximum)			200				
PS Throughput			275 Mbps				
Antivirus Throughput (Proxy Based / Flow Based)			35 / 65 Mbps				
CAPWAP Clear-text Throughput (HTTP)	210 Mbps						
Virtual Domains (Default / Maximum)							
Maximum Number of FortiAPs (Total / Tunnel Mode)			32 / 16				
Maximum Number of FortiTokens			100				
Maximum Number of Registered FortiClients			200				
High Availability Configurations	Active / Active / Passive, Clustering						
Dimensions				9			
	1 70 0 5 0 70	1 70 0 0 0 70	1 70 0 5 0 70	1 70 0 0 0 70	1 70 17 10 51		
Height x Width x Length (inches)	1.72 x 8.5 x 8.78	1.72 x 9.2 x 8.78	1.72 x 8.5 x 8.78	1.72 x 9.2 x 8.78	1.72 x 17 x 10.51		
Height x Width x Length (mm)	44 x 216 x 223	44 x 234 x 223	44 x 216 x 223	44 x 234 x 223	44 x 432 x 277		
Form Factor	Desktop	Desktop	Desktop	Desktop	1 RU		
Weight	3.5 lbs (1.6 kg)	3.5 lbs (1.6 kg)	3.5 lbs (1.6 kg)	3.5 lbs (1.6 kg)	10.6 lbs (4.8 kg)		
Environment							
Power Required			100-240V AC, 50-60 Hz				
Maximum Current	110 V / 1.5 A, 220 V / 0.75 A	110 V / 1.5 A, 220 V / 0.75 A	110 V / 2 A, 220 V / 1 A	110 V / 2 A, 220 V / 1 A	110V / 5.4 A, 220 V / 2.9 A		
Total Available PoE Power Budget	-	-	61.6 W	61.6 W	200 W		
Power Consumption (Average / Maximum)	18 / 22 W	21 / 25 W	59 / 89 W	60 / 90 W	156 / 256 W		
Heat Dissipation	74 BTU / h	85 BTU/h	303 BTU/h	307 BTU/h	874 BTU/h		
Operating Temperature			32-104°F (0-40°C)				
Storage Temperature			-31–158°F (-35–70°C)				
Humidity			20-90% non-condensing				
Operating Altitude			Up to 7,400 ft (2,250 m)				
Compliance							
	FCC Part 15 Class B/A, C-Tick, VCCI, CE, UL/cUL, CB						

Certifications

ICSA Labs: Firewall, IPsec, IPS, Antivirus, SSL-VPN

Note: All performance values are "up to" and vary depending on system configuration. Antivirus performance is measured using 44 Kbyte HTTP files. IPS performance is measured using 1 Mbyte HTTP files. IPsec VPN performance is based on 512 byte UDP packets using AES-256+SHA1.



GLOBAL HEADQUARTERS EMEA SALES OFFICE

Fortinet Inc. 899 Kifer Road Sunnyvale, CA 94086 United States Tel: +1.408.235.7700 Fax: +1.408.235.7737

06560, Sophia Antipolis, France Tel: +33.4.8987.0510 Fax: +33.4.8987.0501

120 rue Albert Caquot 300 Beach Road #20-01 The Concourse

Singapore 199555 Tel: +65.6513.3730 Fax: +65.6223.6784

APAC SALES OFFICE

LATIN AMERICA SALES OFFICE

Prol. Paseo de la Reforma 115 Int. 702 Col. Lomas de Santa Fe, C.P. 01219 Del. Alvaro Obregón México D.F. Tel: 011-52-(55) 5524-8480

Copyright© 2014 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiGate®, FortiGate® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.

FST-PROD-DS-GT90D FGFWF-90D-DAT-R7-201411